WESTERN POWER DISTRIBUTION INNOVATION TEAM

OPENLV BACKGROUND

BALANCING ACT NOVEMBER 2019

DAVID RUSSELL PROJECT MANAGER TIM BUTLER
TECHNICAL LEAD





OPENLY BACKGROUND



OVERVIEW

Project Aims:

- Open up live data from electricity networks
- Trial an open, flexible platform that could be deployed to every LV substation in Great Britain
- Show how 3rd parties can develop software applications to be deployed in LV substations
- Demonstrate the platform's ability to provide benefits to the network, operators, community groups and wider industry

Funding: Network Innovation Competition


Delivery: WPD & EA Technology

Timescales: December 2016 to May 2020






THE CONCEPT










RELEASING ADDITIONAL CAPACITY



What


- Check network capacity against RTTR of transformer; when breached, close two radial circuits to mesh the LV network
- Deploy two proven techniques
 - 'Dynamic Thermal Ratings app' and
 - 'Network Meshing app'

How

- Assess WPD's network to identify candidate circuits
- Target a range of LV networks
- Deploy LV-CAP™ to 60 substations
- Deploy network automation to 10 substations (5 pairs)
- Monitor how the solution operates over the trial period
- Assess and report on performance




MESHING THE NETWORK





COMMUNITY ENGAGEMENT



What


- To work with key community groups to understand whether apps can be developed and installed on the platform
- Identify funding sources that customers / communities can use to develop specific apps

How

- Community engagement to promote availability of platform / LV network data
- Make available 10 LV-CAP™ units for deployment
- Funding to develop specific apps to be raised outside of the project budget, e.g. public funding / private sector



BUSINESS & ACADEMIA



What


 To enable companies to develop innovative algorithms and applications for either the DNO, or its customers

How

- Publicise the opportunity to 3rd parties
- Make available 10 LV-CAP™ devices for substation deployment
- Funding to develop specific apps to be raised outside of the project budget



SYSTEM ARCHITECTURE







OPENLV HARDWARE

- Intelligent Substation Device (ISD) Enclosure
 - LV-CAP™ platform
 - Communications
- Monitoring
 - Lucy Electric GridKey MCU520
 - Thermocouple sensors
- LV Network Automation
 - ALVIN Reclose[™] devices














OPENLV SOFTWARE





WHEN ARE WE DOING IT?

Phase 1 Mobilise & Procure

Set Up full Project Team (Jan-17 to Jul-17)

Phase 2 Design & Build

- Central Infrastructure (Mar-17 to Sep-17)
- Initial Field Tests (Oct-17 to Jan-18)
- Hardware Available for All Methods (Dec-17)

Phase 3 Trial, Consolidate & Share

- Project Trial Period (Mar-18 to Oct-19)
- Reporting and Dissemination (Nov-19 to Apr-20)





CORE DELIVERABLES

1. Specification, design and Factory Acceptance Testing of the overall Solution (Oct-17)

2. Detailed trial design identification of target networks and assessment of market potential (May-18)

3. Learning from deployment of the Solution & standard guidelines for app development (Feb-19)

4. Learning from the project trials (Jan-20)

5. Knowledge capture, dissemination & transfer to BaU (Apr-20)



KEY COMPANIES/SUPPLIERS
























OPENLV: METHOD 1 - PURPOSE

- Network Assessment
- Capacity Release
- BAU Comparison
- Plus additional specific technical learning.







OPENLV: METHOD 1 - DEPLOYMEN

Simulation Units



Autonomous Control









OPENLV: METHOD 1 – AUTOMATED SWITCHING METHODOLOGY






Office based machine


























OPENLV: METHOD 1 – LEARNING

- Method 1 specific:
 - Meshing network as a standalone operation.
 - Dynamic Thermal Rating.
 - Predicting and responding.
- But...
 - Active control sites were chosen to test the 'proof of concept' in a safe manner.
 - Not representative of locations that may require support.
- Distributed Intelligence works
 - · Reduced data transmission.
 - Deployable to areas with suboptimal communications.
 - Configurable to suit the needs of individual substations.
 - · Measurable benefits without human interaction.

Leave platform
in place to
monitor
situation and
report if further
issues arise



Deploy algorithm, app, or additional controllable hardware



identified

Potential issue



Deploy
Distributed
Intelligence
Platform

